



FEATURES

- **Industry Grade GPS Antenna**
- **Rugged Weatherproof plastic housing**
- **Provides Positional Data in AIS Transmissions**
- **Fully waterproof (IP67)**
- **Low noise integrated amplifier**
- **Voltage: 2.5 – 5.5 V dc**
- **Storage temperature: -40°C to +100°C**
- **High performance GPS patch antenna**

ANTENNAS & AERIALS

AG100 GPS ANTENNA

SKU: 001-1030

[View Online >](#)

OVERVIEW

The AG100 is a GPS antenna for use with the T200B Class B AIS Transceiver and all Comar AIS receivers with a GPS input.

A high performance GPS patch antenna and a low noise amplifier are integrated into a fully waterproof enclosure, providing excellent antenna signal amplification and out-band filtering with rejection. Supplied with external flagpole-style mount for cabin-roof mounting.

APPLICATIONS

- For providing Positional Data in AIS Transmissions
- Improving Safety at Sea

RELATED PRODUCTS

AV400 - Commercial Antenna for AIS

AV300 - Fibreglass VHF antenna

AV100 - Masthead Antenna, Stainless Steel Whip

Comar's range of AIS Transponders

PHYSICAL

Weight:	150 g (without cable)
Dimensions:	Antenna: Dia. 80 mm H 71.3 mm
Mounting:	1 Inch 14 TPI threaded mountured
Mounting Base:	W 110 mm L 70 mm H 75.2 mm
Construction:	Plastic, Centre-fed TNC connector for antenna output

ENVIRONMENTAL

Operating Temp:	-30 °C to +80 °C
Storage Temp:	-40 °C to +100 °C
Relative Humidity:	40% to 95% non-condensing
Water Resistance:	100% waterproof IP67

ELECTRICAL

Supply Voltage:	5.0 V dc
Current Consumption:	18 mA @ 5.0 V dc
VSWR:	1.5 max
Output Impedance:	50 Ω
Center Frequency:	1575.42 MHz
Gain:	30 +/-4.5 dB
Noise Figure:	2.0 max
Bandwidth:	2 MHz min.
Cable:	10 metre RG58 A/U
Connections:	TNC connector



Copyright © 2018 Comar Systems Ltd. - AG100 Datasheet v06r02

Vittlefields Technology Centre, Forest Road, Newport, Isle of Wight, United Kingdom. PO304LY
Comar Systems Ltd. reserves the right to make changes to its products and specifications without prior notice.